



MY BOOM AF Offshore – Air Inflatable Containment boom

- **My-Boom AF** is a lightweight rapid response boom - ideal for operations in coastal waters and offshore
- **My-Boom AF** is made of a highly flexible material and has good wave following characteristics
- **My-Boom AF** has segmented air chambers each 3.8 m long – each with one Monsun air valve. End connectors are ASTM F2438-04 Slide type.
- **My-Boom AF** is made of polyester fabric covered with orange coloured 100% Polyurethane and has a hot dip galvanized grade 30 chain as ballast weight.
- The **My-Boom AF** range of booms provides simple and effective containment boom solution. It is designed for optimum performance, quick deployment from a reel and low storage volume. For operation of the reel and inflation of the boom a range of power packs is available

My-Boom AF Ocean is available in two standard sizes: 1.1 m and 1.7 m inflated overall width. It is lightweight and quick to deploy and can be pulled very rapidly into the water, either from a containerized or an open boom reel. The average deployment time is 15 to 20 minutes for 200 metres, depending on the experience of the operators and the accessories included in the system. Minimum size power pack is 7.3 kW and up to 35 kW power pack are available for operation of for example skimmers too.



	My-Boom 1100 AF	My-Boom 2000 AF
Boom height, operational	1100 mm (42")	1700 mm (66")
Freeboard	430 mm (17")	600 mm (24")
Draught	670 mm (25")	1100 mm (42)
Fabric weight	1050 - 1200 g/m ²	
Reinforcement fabric	Polyester 1100 dtex	
Fabric tensile strength	120 kN	
Colour	Orange	
Standard section length	25 m and 33.3 m	
Air chamber length	3.8 m	
Air valve	Monsun XG non return valve	
End connectors	ASTM slide connector	
Ballast chain	9mm (3/8") hot galvanized	13mm (1/2") hot galvanized G30
Boom Weight	4,5 kg/m	8.2 kg/m
Buoyancy to weight ratio	20:1	32:1

*



My-Boom AF - Offshore

EEXII-Manufacturing, Sdn, Bhd
 No. 32 Jalan Bagan Nira, 26/8,
 Hicom Industrial Park, Section 26,
 40000 Shah Alam
 Tel: 603-5192 2913 Fax: 603-5192 9913
 Email : sales@eexii-manufacturing.com