

## MY BOOM - Rapid Response Containment boom



- **My-Boom** is a light weight rapid response boom - ideal for operations in ports, harbors, coastal areas where a quick response is required.
- Handles are provided approximately every meter along the top of the boom.
- **My-Boom** has symmetrical closed cell floats that allow the boom to be wound up onto boom reels or packed into racks and containers.
- **My-Boom** is made in orange PVC/PU coated polyester with two or three webbing bands for added tensile strength.
- **Effective, reliable design**
- The **MY-BOOM** range of booms are designed to provide simple and effective containment boom for harbours and marinas, enclosed coastal waters, rivers, estuaries, API separators, industrial ponds and lagoons. It is designed for optimum performance, quick deployment from a reel and low storage volume.

**My-Boom** is available in six standard sizes: 0.3, 0.5, 0.6, 0.8, 0.95 and 1.1 meter overall width. It is lightweight and quick to deploy, and as it does not require any special machinery to deploy and can be pulled very rapidly into the water, either from a container or boom reel and right from the beach. The average deployment time is 3 to 5 minutes for 200 metres.



**TECHNICAL SPECIFICATIONS**

MYBOOM	300	500	600	800	950	1100
Overall	0.3m / 12"	0.5m / 20"	0.61m / 24"	0.8m / 32"	0.95m / 38"	1.1m/44"
Freeboard	0.1m / 4"	0.15m / 6"	0.20m / 8"	0.25m / 10"	0.35m / 13"	0.4m/16"
Ballast chain galv	7 mm	7 mm	7 mm	10 mm	13 mm	13 mm
Section*	15, 25 m (50'/82')					
Connector	ASTM quick (Z) is standard, ASTM Slide optional					
Boom Weight	2 kg/m	2.4kg/m	2.9kg/m	4.2kg/m	4.5kg/m	5.1kg/m
Storage Options	Bag, Reel	Bag, Reel or Rack	Reel or rack	Reel or Rack	Reel or Rack	Reel

\*Other section lengths are provided to order.

Standard Boom Material: 750g m<sup>2</sup> knitted polyester fabric impregnated with PVC/PU and reinforced with 3 reinforcement webbings – alternative fabric 1000 g/m<sup>2</sup>

Boom Wall Supports: Vertical fiberglass lattices.

Buoyancy: Closed cell polyethylene foam rectangular panel floats – 2 in each pocket

Hand Holds: Webbing loops approx. every meters along the top of the boom.

Ballast: Galvanized ballast chain inside pocket alternatively

Section end connector: ASTM quick connector

Standard Colours, Bright 'safety' Orange.



**PVC/PU SOLID FLOAT CURTAIN BOOMS**

**EEXII Manufacturing Sdn, Bhd**

No. 32 Jalan Bagan Nira, 26/8,  
Hicom Industrial Park, Section 26, 40000 Shah Alam  
Tel: 603-5192 2913 Fax: 603-5192 9913  
Email : [sales@eexii-manufacturing.com](mailto:sales@eexii-manufacturing.com)